



SAFETY DATA SHEET Sure-Set™Acrylic CIC-1200A Part B

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

<u>Product identifier</u> SURE-SET[™] ACR part B

Product name

Recommended use of the chemical and restrictions on use

Application Catalyst.

Details of the supplier of the safety data sheet

Supplier Aerosmith Fastening System

5621 Dividend Road.

Indianapolis, Indiana 46241

Tel: 800.528.8183 Fax: 317.390.6980

email:info@aerosmithfastening.com www.aerosmithfastening.com

Contact Person: Chemtrec:

Emergency telephone number Chemtrec: 1-800-424-9300 (Within Continental (USA);

Emergency telephone Chemtrec: 703-527-3887 (Outside USA).

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Eye Irrit. 2A - H319 Skin Sens. 1 - H317

Human health May cause skin disorders if contact is repeated or prolonged. May irritate eyes and skin.

Environmental The product contains a substance which is very toxic to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

Physicochemical Not considered to be a significant hazard due to the small quantities used.

Label elements

Pictogram



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Revision date: 8/14/2018 Supersedes date: 6/14/2018



Sure-Set™ Acrylic CIC-1200A Part B

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P411 Store at temperatures not exceeding 25°C /77°F.

Contains BENZOYL PEROXIDE

3. Composition/information on ingredients

Mixtures

GLYCERINE 20-50%

CAS number: 56-81-5

BENZOYL PEROXIDE 10-15%

CAS number: 94-36-0

BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR

1-5%

CAS number: 670241-72-2

ZINC DISTEARATE 1-5%

CAS number: 557-05-1

CARBON BLACK <0.5%

CAS number: 1333-86-4

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation.

Eye contact Irritation of eyes and mucous membranes.

Revision date: 8/14/2018 Supersedes date: 6/14/2018



Sure-Set™ Acrylic CIC-1200A Part B

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

Special hazards arising from the substance or mixture

Specific hazards No specific precautions due to the small quantities handled.

Hazardous combustion

products

Oxides of carbon.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. For waste disposal,

see Section 13.

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame.

Advice on general

Do not eat, drink or smoke when using this product. No specific hygiene procedures

occupational hygiene recommended but go

recommended but good personal hygiene practices should always be observed when working

with chemical products.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from flammable and combustible materials. Store in closed original container at

temperatures between 44°F and 77°F.

Storage class Chemical storage.


Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits





Sure-Set™ Acrylic CIC-1200A Part B

GLYCERINE

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m3

Α4

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³

CARBON BLACK

Long-term exposure limit (8-hour TWA): OSHA 3.5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 3 mg/m³ inhalable fraction

A3

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Wear protective gloves made of the following material: Nitrile rubber.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. DO NOT

SMOKE IN WORK AREA!

Respiratory protection No specific recommendations.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid

Color Black.

Odor Characteristic.

Odor threshold Not determined.

pH 5 - 6

Melting point Not applicable.

Initial boiling point and range Not applicable.

Flash point Not applicable.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not determined.



Supersedes date: 6/14/2018

Sure-Set™ Acrylic CIC-1200A Part B

Upper/lower flammability or

explosive limits

Not determined.

Other flammability Not determined.

Vapor pressure Not determined.

Vapor density Not determined.

Relative density 1.5 - 1.6

Bulk density Not applicable.

Solubility(ies) Not determined.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature >50°C

Viscosity > 60 S ISO2431

Explosive properties No information available.

Oxidizing properties Not determined.

10. Stability and reactivity

Reactivity The following materials may react with the product: Acids. Alkalis. Amines. Strong reducing

agents.

Stability Stable at normal ambient temperatures and when used as recommended. Will decompose at

temperatures exceeding 50°C.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid contact with strong reducing agents. Avoid heat. Avoid contact with acids and alkalis.

Materials to avoid Strong reducing agents. Acids, non-oxidizing. Acids - organic. Alkalis - inorganic. Alkalis -

organic. Amines.

Hazardous decomposition

products

Oxides of carbon.

11. Toxicological information

Information on toxicological effects

Skin sensitization

Skin sensitization Sensitizing.

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin Contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Route of exposure Skin and/or eye contact.

Supersedes date: 6/14/2018



Sure-Set[™] Acrylic CIC-1200A Part B

Medical Symptoms Skin irritation. Irritation of eyes and mucous membranes.

Medical considerations No information available.

12. Ecological information

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not determined.

Mobility in soil

Mobility Mobile. The product is partly miscible with water and may spread in the aquatic environment.

13. Disposal considerations

Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Dispose of waste via a licensed waste disposal contractor.

14. Transport information

UN Number

UN No. (TDG) 3082 UN No. (IMDG) 3082 UN No. (ICAO) 3082

UN No. (DOT) UN3082

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9



Sure-Set[™] Acrylic CIC-1200A Part B

Transport labels



DOT transport labels



Packing group

TDG Packing Group

IMDG packing group III

ICAO packing group

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

ZINC DISTEARATE

1.0 %

1-5%

BENZOYL PEROXIDE

1.0 %

10-15%

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.



FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

The following ingredients are listed or exempt:

BENZOYL PEROXIDE

Threshold Quantity: 7500 lbs

10-15%

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

CARBON BLACK

Carcinogen.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

BENZOYL PEROXIDE

Present.

10-15%

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

GLYCERINE

Present.

20-50%

ZINC DISTEARATE

Present.

1-5%

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%



Sure-Set[™] Acrylic CIC-1200A Part B

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

GLYCERINE

Present.

20-50%

ZINC DISTEARATE

Present.

1-5%

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

GLYCERINE

Present.

20-50%

ZINC DISTEARATE

Present.

1-5%

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

GLYCERINE

Present.

20-50%

ZINC DISTEARATE

Present.

1-5%

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%


Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

GLYCERINE

Present.

20-50%





Sure-Set ™ Acrylic CIC-1200A Part B

ZINC DISTEARATE

Present.

1-5%

CARBON BLACK

Present.

<0.5%

BENZOYL PEROXIDE

Present.

10-15%

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

16. Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 8/14/2018

Version number 2.002

Supersedes date 6/14/2018

SDS No. 20673

Hazard statements in full H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.